

# DECLARATION OF PERFORMANCE

## DoP No. 099-02 Bekatherm EPS F

Expanded polystyrene panels

1. Name and/or designation of the construction product type

**Bekatherm EPS F**

2. Type, batch or serial number or some other element that enables the identification of the construction product:

**Stamped on the packaging.**

3. Intended use or uses of the construction product in accordance with the appropriate technical specification or technical regulation:

**White thermal insulation panels made of expanded polystyrene, intended for use in thermal insulation facade systems ETICS according to ETAG 004.**

4. Name and address of the manufacturer:

**Banja Komerc Bekament DOO,  
Kralja Petra Prvog 132,  
34304 Banja, Arandjelovac, Serbia**

5. Name and address of representative: /

6. System or systems of assessment and verification of the constancy of performance of the construction product (AVCP), established by the appropriate technical specification or technical regulation:

**System 3**

7. Applied technical regulations:

**EN 13163:2012+A1:2015**

8. List of essential characteristics and performance of essential characteristics:

**Product label: EPS-EN 13163-L2-W2-T1-S2-P3-DS(N)2-DS(70,90)1-CS(10)70-BS135-TR120-WL(T)3,5**

Characteristi	Label	Unit	Declared	Tolerance	Harmonized
---------------	-------	------	----------	-----------	------------

CS					technical specification
Length	L	mm	L2	±2	EN 822
Width	W	mm	W2	±2	EN 822
Thickness	T	mm	T1	±1	EN 823
Rectangularity	S	mm/m	S2	±2	EN 824
Flatness	P	mm	P3	±3	EN 825
Dimensional stability	DS(N)	%	DS(N)2	±0,2	EN 1603
Dimensional stability at certain temp. and moisture.	DS(70,90)	%	DS(70,90)1	≤1	EN 1604
Compressive strength at 10% deformation	CS(10)	kPa	CS(10)70	≥70	EN 826
Tensile strength perpendicular to the surface	TR	kPa	TR120	≥120	EN 1607
Flexural strength	BS	kPa	BS135	≥135	EN 12089
Long-term water absorption during immersion	WL(T)	%	WL(T)3,5	≤3,5	EN 12087
Thermal conductivity coefficient	$\lambda_D$	W/mK	0,039	/	EN 12667
Fire reaction	/	/	Euroclass E	/	EN 13501-1

Panel thickness, mm	d	20	30	40	50	60	70	80	90	100	110
Lambda/thickness W/m <sup>2</sup> K	$\lambda_D/d$	1.95	1.30	0.98	0.78	0.65	0.56	0.49	0.43	0.39	0.35
Thermal resistance, m <sup>2</sup> K/W	$R_D$	0.50	0.75	1.00	1.25	1.50	1.75	2.05	2.30	2.55	2.80

Panel thickness, mm	d	120	130	140	150	160	170	180	190	200
Lambda/thickness W/m <sup>2</sup> K	$\lambda_{D/d}$	0.33	0.30	0.28	0.26	0.24	0.23	0.22	0.21	0.20
Thermal resistance, m <sup>2</sup> K/W	R <sub>D</sub>	3.05	3.30	3.55	3.85	4.10	4.35	4.60	4.85	5.10

**9. The initial product type test was performed by the Institute IGH, d.d., 1 Janka Rakuše Str., 10000 Zagreb, Croatia (NB 2477) and the Report on the evaluation of the properties of the construction product OD-DC 15/016-014 was issued.**

**Product testing was conducted by the Institute for Materials Testing a.d. in Belgrade and the Test Report was issued under the number DSM-111/22, 20.10.2022, and GFT-8306/22-TOL, 14.10.2022.**

The characteristics of the product are in accordance with the characteristics specified in clause 8.

This performance declaration is published in accordance with the Law on Construction Products (Official Gazette of RS, No. 83 of October 29, 2018) and EU Regulation, CPR 305/2011, and is solely the responsibility of the manufacturer specified in clause 4.

Name and function:

Lena Riznić, QQ Sector Director

Signed

Round official seal: BANJA komerc BEKAMENT doo V  
Banja Arandjelovac



2477

In Banja

11.04.2024.

Previous version: 18.07.2023.

Modified chapters: 8.

