

1. PRODUCT AND COMPANY INFORMATION

Commercial product name: BK-Deco Acryl

Manufacturer:

Banja Komerc Bekament DOO
34304 Banja
Arandelovac
tel. 034-6777-500
fax. 034-6777-505
e-mail: komercijala@bekament.com

TDS contact: email: laboratorija@bekament.com

2. DESCRIPTION, FIELD OF APPLICATION

BK-Deco Acryl is a high-quality acrylic emulsion-based primer used for leveling off the surface, neutralization, and increasing the adhesion of internal decorative paints. Because it possesses fine particles, it creates a mild relief onto which these materials are easily applied.

It is considered an eco-product not harmful to human health or the environment. It does not contain organic solvents.

3. COMPOSITION

Chemical composition: Aqueous polymer emulsion, water, additives, pigments, and mineral fillers.

Hazardous substances: In accordance with the (EC) Regulation No. 1272/2008 on classification, labelling and packaging of substances and mixtures, through which the CLP/GHS classification and labeling system was introduced into law, this product is not classified as a hazardous product.

4. TECHNICAL CHARACTERISTICS

Density, g/dm³ (EN ISO 2811-1)	1,400-1,600
Viscosity, mPas (EN ISO 2555)	5,000-10,000
Adhesion to the surface, MPa (EN ISO 4624)	≥ 1,0
Indicative consumption, ml/m²	~130-150
Packaging, l	1;

TECHNICAL DATA SHEET	Edition: 2	Version: 2
BK-DECO ACRYL	RZ-TLP-050	Date: April 04 2023

5. OTHER CHARACTERISTICS

Physical appearance: White or colored viscous liquid

Odor: Specific of polymeric binders

pH value (EN ISO 787-9): 8-9

Dry matter content (EN ISO 3251), %: ~61

VOC* content, g/l: < 1 (maximum value allowed A (g) 30 g/l)

*VOC: Volatile Organic Compound;

Possibility of choosing shades according to Bekament's Decorative color charts in 54 shades. BK-Deco Acryl may also be colored using the BK- Color shading product. We do not guarantee a complete match according to the color charts of other manufacturers, nor do we guarantee absolute repeatability of shades.

6. SURFACE PREPARATION

The surface to which the primer is applied must be firm, clean, and dry, without poorly bound parts, greasy stains, etc. All surfaces smoothed using quality smoothing coats such as BK-GletEx Universal or BK-GletEx Acryl (age depends on the type), gypsum-cardboard panels, as well as surfaces where dispersion paints had taken solid hold, etc. are appropriate surfaces.

All old, poorly accepted coatings need to be removed, repaired with a suitable material and only then proceed with the application of the substrate.

In case of repainting the surfaces infected with wall molds, it is necessary to disinfect with BK-Sanacid.

When the surfaces in question have been previously treated with oil-based paints, varnishes, etc, a complete removal of all existing spreads must be performed.

7. PREPARATION AND APPLICATION

The mass must be stirred before use. After that, dilute the mass with about 10% (0,1l) of water. The primer is usually applied using a long-haired roller or a brush (apply using criss-cross hand motions; additional structure is created in such a manner).

The drying time under normal conditions (T=+23-25 °C, relative humidity=50-60%), before applying the paint or mortar is at least 6 hours. If the primer is being coloured, the maximum amount of BK-Color for toning the BK-Deco Acryl base is 1/2 of the vial.

Air and surface temperature during installation should be in the +5 °C to +30 °C range. High moisture and low temperatures may significantly lengthen the drying time.

8. CLEANING THE TOOLS

All tools must be thoroughly washed using water immediately after use. If the tools are not washed immediately after use, remove the hardened residue mechanically. Removal may be easier if the tools are submerged in water over a period of several hours.

9. HANDLING AND STORAGE

No special caution during use is needed when using the product properly. Keep out of reach of children.

Store at temperatures between +5 ° C and +25 ° C, protected from direct sunlight and frost.

Shelf life: 18 months.

10. PERSONAL PROTECTION

Respiratory tract protection: Not needed when the rooms are well aerated.

Hands and body protection: When the skin is repeatedly exposed to the mass, a preventative use of protection gloves is recommended. Use long-sleeve work overalls.

Eye protection: Use safety goggles as a preventative measure.

11. ECOTOXICOLOGICAL INFORMATION

Based on experiences and information currently available, no negative health effects are known when the product is used appropriately. Prevent uncontrolled discharge into sewage and waterways.

12. STORAGE

In accordance with local/regional/European/national regulations.

13. OTHER INFORMATION

If the contractor notices an aesthetic or application deficiency while using the material, he is obliged to cease the works and notify the manufacturer of this. The manufacturer will consider the claim in the shortest possible time frame. Complaints to the manufacturer upon using a significant portion or the entire amount of the materials are not subject to claims.

14. NOTE

Banja Komerc Bekament DOO performs product quality checks using its own laboratories. It also regularly tests its products in certified laboratories. The Data Sheet is the product of our knowledge and previous practical experience. The purpose of the Data Sheet is to serve as a recommendation in order to achieve the best possible results. If weather and other conditions are different than those described in our instructions, our instructions need to be taken as general guidelines, without an installation warranty.

Banja Komerc Bekament DOO assumes no liability for damages resulting from the improper use or incorrect product selection, as well as for poorly executed work. It is assumed that the contractor has mastered the techniques of installing and use of various products.

RZ-TLP-050

Banja Komerc Bekament d.o.o., Banja / 34304 Arandelovac | www.bekament.com

TECHNICAL DATA SHEET	Edition: 2	Version: 2
BK-DECO ACRYL	RZ-TLP-050	Date: April 04 2023

Matters written herein bind us in no way.

This document replaces all previous versions, which as of the above date of making of this one are considered invalid.

Date: January 17 2022.

Previous version: Version 2.0-24.12.2021.

Amended chapters: 2.