

<b>TECHNICAL DATA SHEET</b>	Issue: 2	Version: 1
<b>BK-GRUND UNIVERSAL</b>	<b>RZ-TLP-003-02</b>	<b>Date: 24.12.2021.</b>

## 1. PRODUCT AND COMPANY INFORMATION

**Product commercial name:** BK-Grund Universal

**Manufacturer:**

Banja Komerc Bekament DOO  
 Kralja Petra Prvog 132  
 34304 Banja  
 Arandelovac  
 tel. 034-6777-500  
 fax. 034-6777-505  
 e-mail: komercijala@bekament.com

**TDS contact:** email: laboratorija@bekament.com

## 2. DESCRIPTION, FIELD OF APPLICATION

BK-Grund Universal is a universal structural primer used for uniforming, neutralization, hardening and adding a waterproof character to the surface before applying acrylic and silicone facade paints and decorative mortars, as well as mineral-based facades. It is considered an eco-product not harmful to human health or the environment. It does not contain organic solvents.

## 3. COMPOSITION

**Chemical composition:** Aqueous polymer emulsion, water, additives, pigments, and mineral fillers.

**Hazardous substances:** In accordance with the (EC) Regulation No. 1272/2008 on classification, labelling and packaging of substances and mixtures, through which the CLP/GHS classification and labeling system was introduced into law, this product is not classified as a hazardous product.

## 4. TECHNICAL CHARACTERISTICS

<b>Density, g/dm<sup>3</sup> (EN ISO 2811-1)</b>	1,550-1,750
<b>Adhesion to the surface, MPa (EN ISO 4624)</b>	≥ 1,0
<b>Water absorption, kg/(m<sup>2</sup> h<sup>0,5</sup>) (EN 1062-3)</b>	0,1-0,5 (Class W <sub>2</sub> according to the EN 1062-1)
<b>Particle size, μm (EN 1524)</b>	< 300 (S <sub>2</sub> according to EN 13300)
<b>Viscosity, mPas (EN ISO 2555)</b>	5,000-10,000
<b>Indicative consumption, g/m<sup>2</sup></b>	~200-250
<b>Packaging, kg</b>	8; 25;

## 5. OTHER CHARACTERISTICS

**Physical appearance:** White or colored viscous

liquid **Odor:** Specific of polymeric binders

**pH value (EN ISO 787-9):** 8-9

**Dry matter content (EN ISO 3251), %:** ~70

**VOC\* content, g/l:** < 2 (maximum value allowed A (g) 30 g/l)

\*VOC: Volatile Organic Compound;

Possibility of choosing 4400 shades. We do not guarantee a complete match according to the color charts of other manufacturers, nor do we guarantee absolute repeatability of shades.

## 6. SURFACE PREPARATION

The surface to which the product is applied must be firm, clean, and dry, without poorly bound parts, greasy stains, etc. Appropriate base are all surface of lime, cement, and cement-lime mortars (at least one month old), concrete surfaces (at least one month old), surfaces smoothed out with quality leveling masses (the age depends on the type), as well as surfaces with colors or mortars which have taken on dispersion colors, etc. All old coatings which did not take proper hold must be removed, shall be repaired with suitable material and then applying access pads.

In the case of painting surfaces infected with wall mold, it is necessary to disinfect with BK-Sanacid. In the case of coating surfaces painted with oily paints, varnishes and similar, it is necessary to completely remove the existing coatings.

## 7. PREPARATION AND APPLICATION

The mass must be stirred before use. After that, dilute the mass with about 15-20% of water (1,2-1,6 l of water for a package of 8 kg; 3,75-5 l of water for a package of 25 kg). The basis is most often applied in a single coating using a long-haired roller or a brush. It is recommended that the BK-Grund Universal shade be of the same shade as that of the final dispersion paint or mortar. As needed, especially in the case of old, highly absorbent surfaces, priming may be performed twice, 2 to 3 hours apart. The drying time in normal conditions (T=+23-25 °C, relative humidity=50-60%), before applying the paint or mortar is at least 12 hours.

Air and basis temperature during installation should be in the +5 °C to +30 °C range. Do not work under direct sunlight, wind, or rain. High moisture and low temperatures may significantly lengthen the drying time.

## 8. CLEANING THE TOOLS

All tools must be thoroughly washed using water immediately after use. If the tools are not washed immediately after use, remove the hardened mechanical residue. Removal may be easier if the tools are submerged in water over a period of several hours.

## 9. HANDLING AND STORAGE

No special caution during use is needed when using the product properly. Keep out of reach of children.

Store at temperatures between +5 ° C and +25 ° C, protected from direct sunlight and frost.

Shelf life: 18 months.

## 10. PERSONAL PROTECTION

Respiratory tract protection: Not needed when the rooms are well aerated.

Hands and body protection: When the skin is repeatedly exposed to the mass, a preventative use of protection gloves is recommended. Use long-sleeve work overalls.

Eye protection: Use safety goggles as a preventative measure.

## 11. ECOTOXICOLOGICAL INFORMATION

Based on experiences and information currently available, no negative health effects are known when the product is used appropriately. Prevent uncontrolled discharge into sewage and waterways.

## 12. STORAGE

In accordance with local/regional/European/national regulations.

## 13. OTHER INFORMATION

Certain deviations of the basis shade in relation to the appropriate shade in the color chart are possible due to the use of natural mineral fillers. Banja Komerc Bekament DOO does not guarantee a complete match of shades from various batches. Deviations in terms of tone are not subject to claims.

If the contractor notices an aesthetic or application deficiency while using the material, he is obliged to cease the works and notify the manufacturer of this. The manufacturer will consider the claim in the shortest possible time frame. Complaints to the manufacturer upon using a significant portion or the entire amount of the materials are not subject to claims.

## 14. NOTE

Banja Komerc Bekament DOO performs product quality checks using its own laboratories. It also regularly tests its products in certified laboratories. The Data Sheet is the product of our knowledge and previous practical experience. The purpose of the Data Sheet is to serve as a recommendation in order to achieve the best possible results. If weather and other conditions are different than those described in our instructions, our instructions need to be taken as general guidelines, without an installation warranty.

RZ-TLP-003-02

Banja Komerc Bekament d.o.o., Banja / 34304 Arandelovac | [www.bekament.com](http://www.bekament.com)

Banja Komerc Bekament DOO assumes no liability for damages resulting from the improper use or incorrect product selection, as well as for poorly executed work. It is assumed that the contractor has mastered the techniques of installing and use of various products.

Matters written herein bind us in no way.

This document replaces all previous versions, which as of the above date of making of this one are considered invalid.

Date: 24.12.2021.

Previous version: 2.0 - 05.11.2020.

Amended chapters: 1