

## DECLARATION OF PERFORMANCE

### DoP No. 048 BK-ParketFix

One-component glue for parquet

1. Name and/or type designation of the construction product:  
**BK-ParketFix**
2. Type, batch or serial number or some other element that enables identification of the construction product:  
**Stamped on the packaging.**
3. Intended use or uses of the construction product in accordance with the relevant technical specification or technical regulation: Intended use or uses of the construction product in accordance with the relevant technical specification or technical regulation:

**Glue intended for gluing classic and lamellar parquet (length up to 400 mm) to cement screeds, concrete and wooden substrates.**

4. Manufacturer's name and address:

**Banja Komerc Bekament DOO,  
132 Kralja Petra Prvog Str.,  
34304 Banja, Arandjelovac, Serbia**

5. Name and address of representative: /
6. System or systems of assessment and verification of the constancy of performance of the construction product (AVCP), determined by the appropriate technical specification or technical regulation:

**System 4**

7. Applied technical regulation:

**SRPS EN 14293:2009**

8. List of essential characteristics and performance of essential characteristics:

Characteristic	Value	Specification
Density, kg/dm <sup>3</sup>	1,4-1,6	EN ISO 2811-1
Shear strength (standard		EN 14293

conditions), N/mm <sup>2</sup> <ul style="list-style-type: none"> <li>• 3 days</li> <li>• 28 days</li> </ul>	>5.0 > 3.5	
Shear strength (standard conditions), N/mm <sup>2</sup> <ul style="list-style-type: none"> <li>• 7 days (standard conditions)</li> <li>• 20 days (+40 ° C)</li> <li>• 1 day (standard conditions)</li> </ul>	> 6	EN 14293
Adhesion to concrete substrate (standard conditions), N/mm <sup>2</sup> <ul style="list-style-type: none"> <li>• 7 days</li> <li>• 28 days</li> </ul>	>2.0 >2.0	EN 14293
Adhesion to concrete substrate, N/mm <sup>2</sup> <ul style="list-style-type: none"> <li>• 7 days (standard conditions)</li> <li>• 20 days (+40 ° C)</li> <li>• 1 day (standard conditions)</li> </ul>	>1.0	EN 14293
Elongation factor	>0.5	EN 14293

**9. The product was tested by the Institute for Material Testing a.d. Belgrade and the Examination Report no. DSM 025/19, 02.04. 2019 was issued.**

The characteristics of the product are in accordance with the characteristics specified in point 8.

This performance declaration is published in accordance with the Law on Construction Products (Official Gazette of RS, No. 83 of 29 October 2018) and EU Regulation, CPR 305/2011 and is solely the responsibility of the manufacturer specified in point 4.

Vesna Jovanović, BSc of technology Eng.  
 Director of development and technical support  
 In Banja  
 03.08.2023.

Signed

Round official seal: BANJA komerc BEKAMENT DOO V  
 Banja Arandjelovac

