

DECLARATION OF PERFORMANCE

DoP No. 147 BK-Pol Protect

Dispersion for interior walls resistant to mold.

1. Name and/or type designation of the construction product:

BK-Pol Protect

2. Type, batch or serial number or some other element that enables identification of the construction product:

Stamped on the packaging.

3. Intended use or uses of the construction product in accordance with the appropriate technical specification or technical regulation:

Dispersion paint based on acrylic binder for interior walls resistant to mold.

4. Manufacturer's name and address:

**Banja Komerc Bekament DOO,
132 Kralja Petra Prvog Str.,
34304 Banja, Arandjelovac, Serbia**

5. Name and address of representative: /

6. A system or systems of assessment and verification of the constancy of performance of the construction product (AVCP), determined by the appropriate technical specification or technical regulation:

System 4

7. Applied technical regulations:

SRPS EN 13300:2023

8. List of essential characteristics and performance of essential characteristics::

Characteristics	Value	Specification
Density, kg/dm ³	1,60 -1,70	EN ISO 2811-1
Maximum particle size, µm	< 100 (fine)	EN 21524

Resistance to rubbing, μm	≥ 70 on 40 cycles (class 5)	ISO 11998
Coverage	$\geq 98 < 99,5$ (class 2 at 6 m^2/l)	ISO 6504-3
Shine	< 5 at the angle 85° (deep matte)	EN 2813
VOC-content, g/l	< 1	max.allowed value A(a), 30 g/l

9. The product was tested by the manufacturer and the product test report II-147 was issued.

The characteristics of the product are in accordance with the characteristics specified in point 8.

This performance declaration is published in accordance with the Law on Construction Products (Official Gazette of RS, No. 83 of 29 October 2018) and EU Regulation, CPR 305/2011 and is solely the responsibility of the manufacturer specified in point 4.

Vesna Jovanović, BSc in Technology Eng.
Director of development and technical support

In Banja
04.08.2023.

Signed

Round official seal: BANJA komerc BEKAMENT DOO V
Banja Arandjelovac

