

# **DECLARATION OF PERFORMANCE**

# DoP No. 092 BK-SuperFlex PU

Polyurethane mass for sealing and gluing

**1.** Name and/or designation of the construction product type:

# **BK-SuperFlex PU**

**2.** Type, batch or serial number or some other element that enables identification of the construction product:

#### Stamped on the packaging.

**3.** Intended use or uses of the construction product in accordance with the appropriate technical specification or technical regulation:

# Sealing compounds for footpaths

#### EN 15651-4: PW-EXT-INT-CC CLASS 20HM

**4.** Name and address of the manufacturer:

For Banja Komerc Bekament DOO, 132 Kralja Petra Prvog Str., 34304 Banja, Aranđelovac, Srbija produces Bostik Benelux BV, Denariusstraat 11, NL-4903 RC Oesterhout

- 5. Name and address of representative: /
- **6.** System or systems of assessment and verification of the constancy of performance of the construction product (AVCP), determined by the appropriate technical specification or technical regulation:

# System 3 System 3 (fire reaction)

7. Applied technical regulations:

#### EN 15651-4:2012

8. List of essential characteristics and performance of essential characteristics: Conditions: Procedure A (according to ISO 8340). Substrates: Mortar M2 (without primer)

Banja Komerc Bekament d.o.o.T +381 34 677 75 00office.prodaja@bekament.comKralja Petra Prvog 132, Banja, Aranđelovac/34304 BanjaF +381 34 677 75 05www.bekament.com

Tekući računi: 205-107631-11 Komercijalna banka, 275-220862016-42 OTP banka Srbija, 160-62023-53 Banca Intesa, 265-1100310004339-30 Raiffeisen banka | Matični broj: 06056091 | Šifra delatnosti: 4690 | PIB: 100997773 | PDV: 131889250



# Classification according to EN 15651-4:2012: PW-EXT-INT-CC, Class 20HM

Characteristics	Value	Specification
Fire reaction class	Class E	-
Release of hazardous substances into the environment and health hazards	NPD (*)	
Water and air permeability		
Tear resistance	Conforms	
Loss of volume, %	≤ 10	
Adhesion/cohesion properties after exposure to water	Conforms, change secant modulus ≤ 50%	EN 15651-4:2012
Adhesion/cohesion properties after exposure to salt water	Conforms	
Tensile properties at sustained elongation after immersion in water	Conforms	
Tensile properties (secant modulus) for use in cold climates (-30°C)	No requirements	
Tensile properties of maintained extension for use in cold climates (-30°C)	Conforms	
Durability	Conforms	

(\*)see the Product Safety Data Sheet

# 9. The initial type test was carried out by the Institute SKZ-TeConA GmbH, Wűrzburg, Germany, NB 1213, which issued the Test Report.

The characteristics of the product are in accordance with the characteristics specified in point 8.

This performance declaration is published in accordance with the Law on Construction Products (Official Gazette of RS, No. 83 of 29 October 2018) and EU Regulation, CPR 305/2011 and is solely the responsibility of the manufacturer specified in point 4.

Vesna Jovanović, BSc in Technology Eng. Director of development and technical support

In Banja 01.08.2023. Signed Round official eal: BANJA komerc BEKAMENT DOO V Banja Aranđelovac

Banja Komerc Bekament d.o.o. Kralja Petra Prvog 132, Banja, Aranđelovac/34304 Banja 🛛 F +381 34 677 75 05 www.bekament.com

T +381 34 677 75 00 office.prodaja@bekament.com

Tekući računi: 205-107631-11 Komercijalna banka, 275-220862016-42 OTP banka Srbija, 160-62023-53 Banca Intesa, 265-1100310004339-30 Raiffeisen banka | Matični broj: 06056091 | Šifra delatnosti: 4690 | PIB: 100997773 | PDV: 131889250