

DECLARATION OF PERFORMANCE

DoP No. 096 BK-UltraX

Polyurethane mass for sealing and gluing

1. Name and/or designation of the construction product type:

BK- UltraX

2. Type, batch or serial number or some other element that enables identification of the construction product:

Stamped on the packaging.

3. Intended use or uses of the construction product in accordance with the appropriate technical specification or technical regulation:

- a. Sealing compounds for facade elements**
- b. Sealing compounds for sanitary joints**
- c. Sealing compounds for footpaths.**

EN 15651-1: F-EXT-INT-CC (CLASS 25HM)

EN 15651-3: S (CLASS XS3)

EN 15651-4: PW-EXT-INT-CC (CLASS 25HM)

4. Name and address of the manufacturer:

For Banja Komerc Bekament DOO, Kralja Petra Prvog 132, 34304 Banja, Arandjelovac, Serbia, produces Bostik Benelux BV, Denariusstraat 11, NL-4903 RC Oesterhout

5. Name and address of representative: /

6. The system or systems of assessment and verification of the constancy of performance of the construction product (AVCP), established by the corresponding technical specification or technical regulation:

System 3

System 3 (fire reaction)

7. Applied technical regulations:

EN 15651-1:2012, EN 15651-3:2012, EN 15651-4:2012



8. List of essential characteristics and performance of essential characteristics:
Conditions: Procedure A (according to ISO 8340).
Substrates: Mortar M1 (with primer P03), Glass (without primer), Anodized aluminum (without primer).

Classification according to EN 15651-1:2012: F-EXT-INT-CC, Class 25HM

Characteristics	Value	Specification
Fire reaction class	Class E	EN 15651-1:2012
Release of hazardous substances into the environment and health hazards	NPD (*)	
Water and air permeability		
Flow resistance, mm	≤ 3	
Loss of volume, %	≤ 10	
Tensile properties at sustained elongation after immersion in water	Conforms	
Tensile properties (secant modules) for application in cold climates (-30°C)	Not required	
Tensile properties of maintained extension for use in cold climates (-30°C)	Conforms	
Durability	Conforms	

(*)see the Product Safety Data Sheet

Classification according to EN 15651-3:2012: S, Class XS3

Characteristics	Value	Specification
Fire reaction class	Class E	EN 15651-3:2012
Release of hazardous substances into the environment and health hazards	NPD (*)	
Water and air permeability		
Vertical flow resistance, mm	≤ 3	
Loss of volume, %	≤ 20	
Tensile properties at sustained elongation after immersion in water	Conforms	
Microbiological growth	3	
Durability	Conforms	

(*)see the Product Safety Data Sheet

Classification according to EN 15651-4:2012: PW-EXT-INT-CC, Class 25HM

Characteristics	Value	Specification
-----------------	-------	---------------

Fire reaction class	Class E	EN 15651-4:2012
Release of hazardous substances into the environment and health hazards	NPD (*)	
Water and air permeability		
Tear resistance	Conforms	
Loss of volume, %	≤ 10	
Tear resistance	Conforms	
Adhesion/cohesion properties on maintained extension after 28 days immersion in water	Conforms, change secant modulus ≤ 50%	
Adhesion/cohesion properties on maintained extension after exposure to salt water	Conforms	
Tensile properties (secant modulus) for use in cold climates (-30°C)	No requirements	
Tensile properties of maintained extension for use in cold climates (-30°C)	Conforms	
Durability	Conforms	

(*)see the Product Safety Data Sheet

9. The initial type test was carried out by the Institute SKZ-TeConA GmbH, Würzburg, Germany, NB 1213, which issued the Test Report.

The characteristics of the product are in accordance with the characteristics specified in point 8.

This performance declaration is published in accordance with the Law on Construction Products (Official Gazette of RS, No. 83 of 29 October 2018) and EU Regulation, CPR 305/2011 and is solely the responsibility of the manufacturer specified in point 4.

Vesna Jovanović, BSc of Technology Eng.
 Director of development and technical support

In Banja
 01.08.2023.

Signed

Round official seal: BANJA komerc BEKAMENT DOO V
 Banja Arandjelovac

