

1. PRODUCT AND COMPANY INFORMATION

Product commercial name: BK-AquaLasur

Manufacturer:

Banja Komerc Bekament DOO
Kralja Petra Prvog 132
34304 Banja Arandelovac
tel. 034-6777-500
fax. 034-6777-505 e-mail:
komercijala@bekament.com

PDS contact: email: laboratorija@bekament.com

2. DESCRIPTION, FIELD OF APPLICATION

BK-AquaLasur is a transparent water-based lasure used for decoration and protection of wood in the external and internal environment. It is good for the decorative protection of windows, doors, window blinds, garden woodwork, cottages, fences, etc. Quality resin, in unison with UV absorbers provides optimal protection of the wood against UV rays, moisture, and other external factors. The product does not have an unpleasant odor.

3. COMPOSITION

Chemical composition: Aqueous polymer emulsion, water, additives, and pigments.

Hazardous substances: In accordance with the (EC) Regulation No. 1272/2008 on classification, labelling and packaging of substances and mixtures, through which the CLP/GHS classification and labeling system was introduced into law, this product is not classified as a hazardous product.

4. TECHNICAL CHARACTERISTICS

density, g/dm³ (EN ISO 2811-1)	1,000-3000
Viscosity, mPas (EN ISO 2555)	5,000-10,000
Indicative consumption, g/m²	60 – 80
Packaging, l	0.65

RZ-TLP-100

Banja Komerc Bekament d.o.o., Banja / 34304 Arandelovac | www.bekament.com

1

5. OTHER CHARACTERISTICS

Physical appearance: Colored liquid

Odor: Specific of polymeric binders

pH value (EN ISO 787-9): 8-9

Dry matter content (EN ISO 3251): ~ 33 %

VOC* content, g/l: 30 (maximum value allowed A (e) 130 g/l)

*VOC: Volatile Organic Compound;

The product is available in 10 shades. It is also available in the form of basis intended for tinting on the Bekament Mix System according to the BK-AquaLasur color chart (51 shades). We do not guarantee absolute repeatability of shades.

6. SURFACE PREPARATION

Wooden surface must be to be dry, clean, and sanded. Old coatings which did not adhere well must be removed, and the surface must be sanded and cleaned from dust. Old coatings which did adhere well should only be matted by sanding and the surface should be cleaned from dust. If tree resin and grease are present, they need to be removed using the BK-Nitro thinner. The level of moisture in conifers must not exceed 15%, while this level is 12 % for deciduous trees. Before applying the first layer of paint on the wooden elements exposed to rainfall, snowfall, and other weather factors, they need to be protected from the effects of fungi, mold, and parasites by applying BKProtecta.

Old cracked, badly-adhered coats needs to be removed first, and surface finely sanded. Well adhered old coats needs to be cleaned and finely sanded.

7. PREPARATION AND APPLICATION

Homogenize the mass by stirring before use. As needed, add water up to 5% (32.5 ml) for application using a brush or a roller, i.e. 10% (65 ml) if using spraying as a method of application. BK-AquaLasur is applied in two layers. Before applying the second layer, a mild sanding of the entirely dry wood area is needed in order to remove the protruding wood fibers. Because the mass becomes dry very quickly, it is recommended to apply the mass in zones without stopping, while possible drops need to be smeared to prevent them from drying. The drying time between layers is 4 to 6 hours in regular conditions (23 °C and 50-60 % relative humidity). Additional corrections to the paint during the installation (additional dilution, adding pigments, etc.) are prohibited.

RZ-TLP-100

Application temperature: 5^oC to +30^oC. Do not work under direct sunlight, rain, strong wind and relative humidity greater than 80 %. The coating achieves its final physical and chemical properties after drying for 28 days in normal conditions (23 °C and 50-60 % relative humidity).

Note: Combine different product batches. In order to achieve the wanted shade, it is very important to homogenize the mixture through stirring. If the mass, due to the extended length of stirring, should contain too much air, **leave it for one hour**, before application and then re-stirr it gently. As a natural material, wood does not have a uniform color, surface, density and absorption. This may result in the fact that the shades of coating deviate from the color chart. Furthermore, besides from the listed facts, the level of dissolution of the coating, the thickness of the layer applied, as well as the color of a previous coating all affect the final appearance of the surface. As the level of dissolution rises, so does the coating transparency. This difference might be even more pronounced among lighter shades. Various kinds of wood, due to their color, have a significant impact on the final appearance of the coating. The color of any possible previous coating may have an impact on the final appearance of the coated surface. Always first apply the paint on a test surface! Dried painted surfaces should not be placed one atop another since "dry adhesion" could occur, especially under greater load and elevated temperature.

8. CLEANING THE TOOLS

All tools need to be thoroughly washed in water immediately after use. If the tools are not washed immediately after use, **remove the hardened residue mechanically**. Removal may be easier if the tools are submerged in water over a period of several hours or if they are washed using the BK-Nitro thinner.

9. HANDLING AND STORAGE

No special caution during use is needed when using the product properly. Keep out of reach of children.

Store at temperatures between +5 ° C and +25 ° C, protected from direct sunlight and frost. **THE PRODUCT MUST NOT FREEZE OVER.**

Shelf life: 18 months.

10. PERSONAL PROTECTION

Respiratory tract protection: Not needed when the rooms are well aerated.

Hands and body protection: When the skin is repeatedly exposed to the mass, a preventative use of protection gloves is recommended. Use long-sleeve work overalls.

Eye protection: Use safety goggles as a preventative measure.

RZ-TLP-100

11. ECOTOXICOLOGICAL INFORMATION

Based on experiences and information currently available, no negative health side effects are known when the product is used appropriately. Prevent uncontrolled discharge into sewage and waterways.

12. STORAGE

In accordance with local/regional/European/national regulations.

13. OTHER INFORMATION

Banja Komerc Bekament DOO does not guarantee a complete match of shades from various batches. Deviations in terms of tone are not subject to claims.

If the contractor notices an aesthetic or application deficiency while using the material, he is obliged to cease the works and notify the manufacturer of this. The manufacturer will consider the claim in the shortest possible time frame. Complaints to the manufacturer upon using a significant portion or the entire amount of the materials are not subject to claims.

14. NOTE

Banja Komerc Bekament DOO performs product quality checks using its own laboratories. It also regularly tests its products in certified laboratories. The Data Sheet is the product of our knowledge and previous practical experience. The purpose of the Data Sheet is to serve as a recommendation

in order to achieve the best results. If weather and other conditions are different than those described in our instructions, our instructions need to be taken as general guidelines, without an installation warranty.

Banja Komerc Bekament DOO assumes no liability for damages resulting from the improper use or incorrect product selection, as well as for poorly executed work. It is assumed that the contractor has mastered the techniques of installing and use of various products.

Matters written herein bind us in no way.

This document replaces all previous versions. All previous versions, starting with the listed date the document was compiled, are void.

Date: 23.12.2021.

Previous version: 1.4 - 14.12.2020.

Amendments: Chapters: 1

RZ-TLP-100