

TECHNICAL DATA SHEET	Issue:1	Version:2
BK-Rustic	RZ-TLP-157	Datum: 09.08.2023.
Izradio: Marija Jovanović	Odobrio: Vesna Jovanović	

1. PRODUCT AND COMPANY IDENTIFICATION

Product trade name: BK-Rustic

Distributor information:

Banja Komerc Bekament DOO
Kralja Petra Prvog 132
Arandelovac
tel. 034-6777-500
fax. 034-6777-505

Contact for TLP production:

e-mail: laboratorija@bekament.com

2. DESCRIPTION AND SCOPE

BK-Rustic is a water-washable paint intended for the decoration of interior surfaces, the application of which gives an attractive appearance to the painted walls.

It is suitable for modern environments that require elegance, both for public places and private homes. BK-Rustic can be washed after three weeks of application, it is characterized by good vapour permeability and is non-flammable. It does not contain solvents and pigments that contain lead and chromium.

3. COMPOSITION

Chemical composition: Organic and inorganic pigments, acrylic emulsion and additives.

Hazardous ingredients: In accordance with Regulation (EC) No 1272/2008 on the classification, packaging and labelling of dangerous substances and mixtures, which legally introduces the CLP / GHS classification and labelling system, this product is not classified as dangerous products.

4. TECHNICAL CHARACTERISTICS

Density, g/cm³ (EN ISO 2811-1)	1000-1100
Viscosity mPas (EN ISO 2555)	30000-40000
Consumption, m²/l	~5

TECHNICAL DATA SHEET	Issue:1	Version:2
BK-Rustic	RZ-TLP-157	Datum: 09.08.2023.
Izradio: Marija Jovanović	Odobrio: Vesna Jovanović	

Package, l	2,5
-------------------	-----

5. OTHER CHARACTERISTICS

Appearance: Pasty mass

Fragrance: Specific to the polymer binder

pH value (EN ISO 787-9): 6,5-7,5

VOC* content, g/l: < 10 (max.permitted value A (I) 200 g/l)

*VOC: Volatile Organic Compound

Possibility of tinting according to Bekament Rustic tone chart. Due to the great influence of the applied application technique on the final appearance of the colour, certain deviations in relation to the shade in the carat tone are possible. We do not guarantee complete reproducibility of shades.

6. SUBSTRATE

The substrate on which the mass is applied must be solid, clean and dry, without loose joints, greasy stains, etc. Suitable substrates are all surfaces levelled with BK-GletEx Universal and BK-GletEx Acryl. Smoothed surfaces should be coated with BK-Deco Acryl primer (drying time min. 6 h). After toning, the mass is mixed slowly, by hand, and after that, the product is ready for use. The product prepared in this way must be used within 15 days.

Depending on the application technique, the substrate can be tinted in only one shade C43 or several shades per tone chart. When levelling surfaces painted with oil paints, varnishes, etc., it is necessary to completely remove the existing coatings.

7. PREPARATION AND APPLICATION

BK-Rustic is available in two techniques: BK-Rustic Art Style 1 and BK-Rustic Art Style 2.

- BK-Rustic Art Style 1 is obtained by applying a base that is toned in the desired shade according to the Bekament Rustic tone chart, and then applied to the toned BK-Deco Acryl foundation C43.
- BK-Rustic Art Style 2 is obtained by applying a non-toned base on a BK-Deco Acryl base which is toned in the desired shade according to the Bekament Rustic tone chart.

After toning, the mass is mixed slowly, by hand, and after that, the product is ready for use. The product prepared in this way must be used within 15 days.

It is applied with a DECOR brush in one or, if necessary, in two layers (for the

TECHNICAL DATA SHEET	Issue:1	Version:2
BK-Rustic	RZ-TLP-157	Datum: 09.08.2023.
Izradio: Marija Jovanović	Odobrio: Vesna Jovanović	

needs of greater fullness), in all directions. When the applied material starts to dry (20-30 minutes after application), light ironing and smoothing are started using Hoble stainless steel 20x8 cm. Ironing can be done in the diagonal direction or all directions, depending on the desired effect.

The coating is completely dry after 24 hours.

The air and substrate temperature during installation should be in the range of +8 °C to +30 °C. The paint is dry to the touch after 6-8 hours, depending on the conditions, while the complete resistance of the film is achieved after 3 weeks.

8. CLEANING OF THE TOOLS

Immediately after use, the tool should be thoroughly washed with water. If the tool is not washed immediately after use, remove hardened residues mechanically. Removal can be facilitated by immersing the tool in water for several hours.

9. HANDLING AND STORAGE

No special handling precautions are required for proper application. Keep out of reach of children.

Store at temperatures from +5 °C to +25 °C, protected from direct sunlight and frost.

Shelf life: 24 months.

10. PERSONAL PROTECTION

Respiratory protection: Not required if the room is well ventilated. Hand and body protection: Preventive use of protective gloves is recommended in case of repeated skin contact. Use a work suit with long sleeves and socks.

Eye protection: Wear safety goggles as a precaution.

11. ECOTOXICOLOGICAL INFORMATION

Based on experience and existing information, no adverse health effects are known when used properly. Prevent uncontrolled discharge into sewers and watercourses.

12. WAY OF DISPOSAL

In accordance with local / regional / European / national regulations.

TECHNICAL DATA SHEET	Issue:1	Version:2
BK-Rustic	RZ-TLP-157	Datum: 09.08.2023.
Izradio: Marija Jovanović	Odobrio: Vesna Jovanović	

13. OTHER INFORMATION

The tone map of decorative materials is made on paper, so when applying decorative materials on different wall surfaces, as well as depending on the application technique, minor deviations of shades from the tone map can be expected, which cannot be the subject of a complaint.

It is desirable to order the total amount of paint for one object at once. Banja Komerc Bekament DOO does not guarantee for complete matching of shades from different batches, deviations in tone cannot be the subject of a complaint.

If the contractor notices any aesthetic or application defect during the installation of the material, he is obliged to suspend the works and inform the manufacturer, who will start considering the complaint as soon as possible. Complaints addressed to the manufacturer after the installation of a larger part or a complete quantity of material, and concerning the stated characteristics, cannot be the subject of a complaint.

14. NOTE

Banja Komerc Bekament DOO performs product control through its own laboratories, as well as regular testing in certified laboratories. The technical sheet is a product of our knowledge and previous practical experience and should be used as a recommendation to all users to achieve the best results. If the weather and other conditions are different from those in our instructions, it is necessary to take our instructions as general guidelines, without a guarantee for installation.

Banja Komerc Bekament DOO does not take responsibility for damage caused by improper use or incorrect selection of products, as well as for poor quality work. It is assumed that the contractor has mastered the techniques of installation and use of various products.

It does not bind us in any way.

Date: 09.08.2023.

Previous version: 1.1. – 24.12.2021.

Amended chapters: 1.