

PRODUCT DATA SHEET	Issue:1	Version:1
BK- Velatura Exclusive	RZ-TLP-163	Date: 02.12.2021.
Prepared by: Marina Radojevic	Approved by: Vesna Jovanovic	

1. IDENTIFICATION OF THE PRODUCT AND THE COMPANY

Trade name of the product: BK-Velatura Exclusive

Data on the manufacturer: Banja Komerc Bekament DOO
Kralja Petra Prvog 132, Banja, Arandjelovac
34304 Banja, Serbia
tel. 034-6777-500
fax. 034-6777-505
e-mail: komercijala@bekament.com

Contact information for the preparation of DSP: e-mail: laboratorija@bekament.com

2. DESCRIPTION AND THE SCOPE

BK-Velatura Exclusive is a semi-transparent acrylic paint resistant to wet wiping intended for special effects in various decorative techniques (BK- Travertino, BK-Natura, BK- Concrete Style). Recommended for indoor use. BK-Velatura Exclusive comes in three shades: silver, gold and combination of the two.

It is classified as ecological product, unarmful to the health of people and the environment.

3. COMPOSITION

Chemical composition: water emulsion of polymers, water, additives and pigments for the effect.

Hazardous ingredients: In accordance with Regulation (EC) No 1272/2008 on classification, packaging and labelling of hazardous substances and mixtures, which in legal terms introduced CLP/GHS classification and labelling system, the product is not classified as hazardous substance.

4. TECHNICAL FEATURES

Density, g/dm³ (EN ISO 2811-1)	1000 - 1100
Viscosity, mPas (EN ISO 2555)	3500 - 6500
Approximate consumption, ml/m²	60- 120
Pakaging, l	1

5. OTHER FEATURES

Appearance: white or toned viscous liquid

Smell: Characteristic to polymer binder

pH value (EN ISO 787-9): 6.50 - 7.50

Dry matter content (EN ISO 3251), %: 25

PRODUCT DATA SHEET	Issue:1	Version:1
BK- Velatura Exclusive	RZ-TLP-163	Date: 02.12.2021.
Prepared by: Marina Radojevic	Approved by: Vesna Jovanovic	

VOC* content, g/l: < 54 (maximum value A (g) 200 g/l)

*VOC: Volatile Organic Compound;

6. SUBSTRATE

The surface on which the substrate is applied must be solid, clean and dry, free from loose parts, greasy stains etc. Suitable substrates are all mineral and organic-based surfaces, where special effects are to be achieved. In case of application to highly absorbent surfaces (e.g. mineral mortars type BK-Travertino, BK-Concrete style) it is necessary to perform surface impregnation with BK-Penetrat (dilute in water in 1:3 ratio) or BK-Ultra Prime in order to decrease and match absorbency, as well as for easy treatment in the application of BK-Velatura Exclusive.

7. PREPARATION AND APPLICATION

BK-Velatura Exclusive is a coating previously prepared for application. If necessary, it can be diluted with water by 20 % (up to 0.2 L of water for packaging). Before use, the mixture should be stirred slightly. Material is applied gradually with a long bristle brush, roller or a sponge to smaller surfaces in the range 1-2 m². While the material is still in form of a paste, the excess should be removed by a sponge or firm plastic spatula, depending on the decorative technique to be coated. Drying rate between the layers of BK-Velatura Exclusive is 4-6 h.

Air and substrate temperatures throughout the application should be in the range between +5 °C and +30 °C. The paint is dry to the touch after 6-8 h, depending on the conditions, while the complete film resistance is achieved 3 weeks later.

8. CLEANING THE TOOLS

Immediately after the use, tools should be thoroughly rinsed in water. If the tools are not washed immediately after the use, mechanically remove any hardened residue. Removal can be facilitated by immersing the tools in water for several hours.

9. HANDLING AND STORAGE

In case of proper application, special precautions are not required for handling. Keep out of reach of children.

Store at temperatures from +5 °C to +25 °C, protected from direct sunlight and the effects of freezing.

Shelf life: 18 months.

10. PERSONAL PROTECTION

Respiratory protection: Not required in case of good ventilation.

Hand and body protection: In case of repeated skin contact, the preventive use of protective gloves is recommended. Use a work suit with long sleeves and legs.

Eye protection: Preventive use of safety goggles.

PRODUCT DATA SHEET	Issue:1	Version:1
BK- Velatura Exclusive	RZ-TLP-163	Date: 02.12.2021.
Prepared by: Marina Radojevic	Approved by: Vesna Jovanovic	

11. ECOTOXICOLOGICAL INFORMATION

Based on experience and existing information, no adverse health effects are known in case of proper use. Prevent uncontrolled discharge into sewerage and watercourses.

12. DISPOSAL METHOD

In accordance with local/regional/European/national regulations.

13. OTHER INFORMATION

If during the application of material the contractor notices any aesthetically or application-related deficiency, the contractor is obliged to cease all the works and notify the manufacturer thereof, who shall take the remarks into consideration as soon as possible. Remarks regarding the specified characteristics submitted to the manufacturer after the incorporation of significant portion or the entire quantity of material cannot be the subject-matter of such complaints.

14. NOTE

Banja Komerc Bekament DOO performs product quality checks in their own laboratories, as well as regular tests in certified laboratories. Data Sheet is the product of our knowledge and previous practical experience intended for all users as a recommendation for achieving the best results. If weather and other conditions are different from those described in our instructions, they should be interpreted as general guidelines, without any installation warranty.

Banja Komerc Bekament DOO assumes no liability for damage resulting from improper use or incorrect selection of product, as well as poorly executed works. It is assumed that the contractor has mastered the techniques of incorporation and use of various products.

The text shall have no legal force under any circumstances.

This document shall replace all previous versions, which shall be considered void from the specified date.

Date of preparation: January 21 2021.

Previous version: 1.0. – 21.1.2021.

Amended chapters: 4